



Low Frequency Ring Mounts

Availability: 4-6 weeks
 Available in Natural Rubber (Other Elastomers Available)

| Part Number | Diameter (A) | Rubber Height (B) | Width (C) | Thred Size | Thred Length (E) | Static Spring Rate LBS/IN | Maximum Load in LBS | Recommended Max. Deflection | Shear |
|-------------|--------------|-------------------|-----------|------------|------------------|---------------------------|---------------------|-----------------------------|-------|
| KR911-55 | .56" | .57" | .28" | 6-32 | .50" | 92 | .75 TO 1 | .035 | .080 |
| KR911-65 | .56" | .57" | .28" | 6-32 | .50" | 136 | 2 | .040 | .060 |
| KR914-55 | .82" | .69" | .34" | 10-32 | .62" | 52 | 2.5 | .090 | .160 |
| KR914-65 | .82" | .69" | .34" | 10-32 | .62" | 82 | 3 | .095 | .120 |
| KR928-55 | 1.10" | .96" | .53" | 1/4-20 | .75" | 188 | 5 | .084 | .150 |
| KR928-65 | 1.10" | .96" | .53" | 1/4-20 | .75" | 192 | 8 | .105 | .115 |
| KR930-55 | 1.69" | 1.70" | .75" | 5/16-18 | .94" | 128 | 13 | .220 | .200 |
| KR930-65 | 1.69" | 1.70" | .75" | 5/16-18 | .94" | 228 | 20 | .260 | .150 |

Karman Rubber
 2331 Copley Road • Akron, OH 44320
 P: (330) 864-2161 • F: (330)864-2124
 Web: www.karman.com
 Email: karman@karman.com